



Cemax 327V

Grinding Aid for Vertical Roller Mill

Uses

For use as a grinding aid for the production of Portland and other hydraulic cements, suitable for enhancing productivity of cement mills.

Description

Cemax 327V is a liquid dispersing agent, for use as a grinding aid for the production of Portland and other hydraulic cements.

Cemax 327V complies with ASTM specification C 465 as a non harmful processing addition. Cemax 327V is a glycol/amine based material.

Properties

Appearance	Pale brown liquid
Specific gravity @20°C	1.05 - 1.15
pH @ 27°C	8.0 -10.0

Standards compliance

Complies with ASTM C465.

Application instructions

Dosage

0.02 - 0.07% by weight, depending on type of clinker, type of mill and desired results.

Estimating

Packaging

Cemax 327V is supplied in 250 kg Drum .

Storage

Since Cemax 327V has a very low freezing point, no anti-freeze protection is needed in bulk installation. Where it is expected that the storage tanks will be exposed to below zero temperatures, provisions should be made for insulating and heating the tank and lines in order to prevent excessive viscosity and to aid pumpability.

Shelf life

Cemax 327V has a shelf life of 6 months if kept in a cool and dry place in unopened containers.

Additional information

Health & Safety

Odour, fumes, spillage : No noxious fumes. If accidentally spilled on skin, wash off immediately with soap and water. If accidentally splashed into eyes, wash out immediately with water, and consult a physician. If accidentally swallowed, induce vomiting and call a physician immediately.

Cemax 327V



Fosroc Chemicals (India) Pvt. Ltd.

Head Office

"Sapthagiri Palace", No.38,
II & III Floor, 12th Cross,
CBI Road, Ganganagar North,
Bangalore 560 032

Important note :

Fosroc products are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale, copies of which may be obtained on request. Whilst Fosroc endeavours to ensure that any advice, recommendation specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products whether or not in accordance with any advice, specification, recommendation or information given by it.

telephone

++91 80-23551500

fax

++91 80-23551510

e-mail

enquiryindia@fosroc.com

Regional Offices

Bangalore

"Sapthagiri Palace", No. 38
II & III Floor, 12th Cross,
CBI Road, Ganganagar North,
Bangalore 560 032.
Ph:080-23551500
Fax : 080-23551510

Mumbai

1401/1402, 14floor,
A-Wing 'The Great Eastern Summit'
Sector-15, CBD, Belapur
Navi Mumbai 400 614
Ph: 022 -43406800-04

Delhi

D-166 Sector 10
Noida,
UP 201 301
Ph:0120-4270620
Fax: 033-2499-0280

Kolkata

304, Jodhpur Park
Kolkata 700 068
Ph:033-65343188