



# Cemax 333

## Grinding Aid and Performance Enhancer

### Uses

For use as a grinding aid for the production of OPC & blended cements.

### Description

Cemax 333 is a liquid dispersing agent, for use as a grinding aid for the production of Portland and other hydraulic cements.

Cemax 333 complies with ASTM specification C 465 as a non harmful processing addition. Cemax 333 is a glycol/amine based material.

### Properties

<b>Appearance</b>	<b>Liquid brown</b>
<b>Specific gravity @20°C</b>	<b>1.104 - 1.106</b>
<b>pH @ 27°C</b>	<b>10.50</b>

### Standards compliance

Complies with ASTM C465.

### Application instructions

### Dosage

0.02 - 0.07% by weight, depending on type of clinker, type of mill and desired results.

### Estimating

### Packaging

Cemax 333 is supplied in 250 kg drum.

### Storage

Since Cemax 333 has a very low freezing point, no anti-freeze protection is needed in bulk installation. Where it is expected that the storage tanks will be exposed to below zero temperatures, provisions should be made for insulating and heating the tank and lines in order to prevent excessive viscosity and to aid pumpability.

### Shelf life

Cemax 333 has a shelf life of 6 months if kept in a cool and dry place in unopened containers.

### Additional information

### Health & Safety

Odour, fumes, spillage : No noxious fumes. If accidentally spilled on skin, wash off immediately with soap and water. If accidentally splashed into eyes, wash out immediately with water, and consult a physician. If accidentally swallowed, induce vomiting and call a physician immediately.

# Cemax 333

---



## Fosroc Chemicals (India) Pvt. Ltd.

### Head Office

"Sapthagiri Palace", No.38,  
II & III Floor, 12th Cross,  
CBI Road, Ganganagar North,  
Bangalore 560 032

### Important note :

Fosroc products are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale, copies of which may be obtained on request. Whilst Fosroc endeavours to ensure that any advice, recommendation specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products whether or not in accordance with any advice, specification, recommendation or information given by it.

### telephone

++91 80-23551500

### fax

++91 80-23551510

### e-mail

enquiryindia@fosroc.com

### Regional Offices

#### Bangalore

"Sapthagiri Palace", No. 38  
II & III Floor, 12th Cross,  
CBI Road, Ganganagar North,  
Bangalore 560 032.  
Ph:080-23551500  
Fax : 080-23551510

#### Mumbai

1401/1402, 14floor,  
A-Wing'The Great Eastern Summit'  
Sector-15, CBD, Belapur  
Navi Mumbai 400 614  
Ph: 022 -43406800-04

#### Delhi

D-166 Sector 10  
Noida,  
UP 201 301  
Ph:0120-4270620  
Fax: 033-2499-0280

#### Kolkata

304, Jodhpur Park  
Kolkata 700 068  
Ph:033-65343188